



CONTEXT

Large accelerators of particles are among the **most complex & expensive tools for scientific discovery.**




Courtesy S. Myers (IPAC 2012)

- Next accelerator at the energy frontier will rely on new technology or new paradigm (e.g. muon accelerators).
- Computer simulations will play:
 - o an increasingly important role in designing, commissioning and operating these very complex machines,
 - o a key role in discovering new technologies.


New technologies (plasmas, dielectric) offer great promise for smaller & cheaper accelerators:

- accelerators based on standard technology are limited by the metallic electrical breakdown limit of ~50-100 MV/m,
- dielectric laser accelerations: a laser propagating through a dielectric lattice can generate electric fields ~ GV/m,
- plasma based acceleration: a driver beam (laser/particles) propagating through a plasma creates a wake with accelerating gradients exceeding 50 GV/m.

Dielectric




Vorpal




ACE3P

Plasmas



Osiris



QuickPIC

METHODS & TOOLS

ComPASS SciDAC-3 will push further the state-of-the-art in modeling of accelerators, using (developing if unavailable):


- the most advanced algorithms & performance optimization on the latest most powerful supercomputers,
- cutting-edge non-linear parameter optimization and uncertainty quantification (UQ) methods.

A comprehensive set of accelerator codes is being developed (ACE3P, Osiris, QuickPIC, Synergia, Vorpal, Warp) that include state-of-the-art electrostatic (ES) & electromagnetic (EM) field solvers:


- ES-multigrid (Synergia, Warp, FASTMath), ES-AMR multigrid (Warp, FASTMath)
- EM-finite element (ACE3P-FASTMath),
- EM-extended stencil finite-difference (Osiris, Vorpal, Warp),
- EM-AMR finite-difference (Warp, FASTMath),
- Darwin-finite-difference (QuickPIC).

Original methods developed under SciDAC-2 will be perfected

- boosted frame
 - o uses special relativity to speed-up calculation by orders of magnitude,
 - o up-to 1 million speedup demonstrated on single 1 TeV stage,
- envelope,
- laser launcher.



Warp simulation of LPA in lab (top) and boosted (bottom) frames.



Vorpal simulation of meter scale LPA stage w/ laser envelope solver.

Capability development with SciDAC institutes:

- **FASTMath:** field solvers (SuperLU, Chombo),
- **QUEST:** uncertainty quantification (QUESO),
- **SUPER:** performance analysis & optimization, non-linear parameter optimization.





Figure Scaling.1: Strong scaling studies on the Blue Waters platform in 2D and 3D using 256 billion particles. OSIRIS has shown to be >93% efficient in 2D and >87% efficient in 3D



APPLICATIONS

New tools will provide unprecedented capabilities that will be used for:

- understanding and optimizing existing accelerators,
- developing new acceleration technologies, (relevant to HEP stewardship of accelerator technology).

The ComPASS SciDAC-3 collaboration has extended experience in the modeling of plasma-based and dielectric laser accelerators.


- accomplishments of the HPC plasma-based acceleration have led to many publications, including some in journals such as Science, Nature, and Physical Review Letters.



With SciDAC-3 tools, the ComPASS collaboration is:

– Plasma-based acceleration:

- o supporting HEP investment in BELLA and FACET experiments,
- o developing techniques to improve beam quality,
- o evaluating options for controlled electron beam injection,
- o improve staging toward future lepton collider concept.




10 GeV BELLA stage (Warp).

FACET stage (QuickPIC).


Colliding pulse injection (Vorpal).

– Dielectric laser acceleration:

- o designing efficient power couplers between optical fiber and accelerator structure,
- o exploring wakefield effects and associated break-ups,
- o designing structures accelerating high quality beams from low to high energy,
- o exploring various topologies (a) 3D silicon woodpile photonic crystal waveguide, (b) 2D glass photonic bandgap hollow-core optical fiber.



VORPAL simulation of a DLA woodpile structure



ACE3P simulation of an improved power coupling scheme for PBG fiber